



information@hydrasearch.com  
+1.410.643.8900

## EF-6-150F-2P – 2-Piece End Fittings – Straight – Flange to Hose (MIL-DTL-24787/1, Type F, Group IX, Class IV, 150 Lb. Flange per MIL-PRF-20042)

SKU: EF-6-150F-2P



### Description

- Use with the following hose: ER512 & 2580

### Specification Table

|                          |                                                                                                                                 |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| pa_applicable-hoses      | ER512 2580                                                                                                                      |
| pa_component-1           | Required per Assembly – 1 Description – Swivel Flange C16913-2 Material – Aluminum Bronze in accordance with MIL-B-24480 C95800 |
| pa_component-2           | Description – Nipple Required per Assembly – 1 D16199 Material – Aluminum Bronze in accordance with MIL-B-24480 C95800          |
| pa_component-3           | Required per Assembly – 2 Description – Segment Material – Aluminum Bronze in accordance with MIL-B-24480 C95800 C22159         |
| pa_component-4           | Description – Bolt Required per Assembly – 4 Material – Monel in accordance with QQ-N-286 C22173-1                              |
| pa_component-5           | Description – Nut Required per Assembly – 4 B16551-3 Material – Monel in accordance with QQ-N-281                               |
| component_pa_component-6 | Description – Washer B16551-2 Material – Monel in accordance with QQ-N-281 Required per Assembly – 4                            |

|                  |                 |
|------------------|-----------------|
| j                | '10.13          |
| k                | '7.38           |
| l                | '8.88           |
| m                | '0.69           |
| n                | '0.56           |
| s                | '6.31           |
| t                | '11.32          |
| a                | '7.03           |
| d                | '2.90           |
| est_wt_lbs       | 51              |
| drawing_number   | C22195          |
| ips_size         | '6              |
| pa_mil-spec      | MIL-DTL-24787/1 |
| no_of_bolt_holes | 12              |