



information@hydrasearch.com
+1.410.643.8900

HSSA-24 – HSSA Series – Super Aquaduct Layflat Hoses

SKU: HSSA-24



Description

- Use with Hydrasearch LFS Elbows and End Fittings. For a complete line of fittings and accessories see Hydrasearch Layflat & Rubber Hose Catalog. Materials: Polyurethane elastomer tube and cover reinforced with high tenacity polyester. Application: Salt and fresh water conveying systems. Operating Temperature Range: -40°F to +200°F

Specification Table

pa_applicable-fittings	Lfs Elbows And End Fittings
application	Salt And Fresh Water Conveying Systems
pa_burst-pressure-psi	600
pa_construction-reinforcement	Polyester
hose_id	'1-1/2
pa_hose-size-dash-no	'-24
drawing_number	'18283
pa_layers-reinforcement	'1
Material	Polyurethane Elastomer Tube And Cover Reinforced With High Tenacity Polyester
pa_max-dimension-a-in	'1.59
pa_max-dimension-b-in	'1.73
pa_min-dimension-a-in	'1-1/2
pa_min-dimension-b-in	'1.64
weight_per_ft_lbs	'0.144

pa_working-pressure-psi	'300
-------------------------	------

HYDRASEARCH