

## HS133-20 – HS133 Series – High Pressure Hoses

SKU: HS133-20



### Description

- Use with Hydrasearch HS1489 Series Fittings. Materials: Synthetic rubber tube and cover reinforced with synthetic fiber. Application: Fresh and salt water systems, hydraulic systems, fuel systems, oil applications and low pressure air. Operating Temperature Range: -40°F to +200°F
- Equal to: FC133
- Mil Number: DTL-24136/2

### Specification Table

pa_applicable-fittings	Hs1489
application	Fresh And Salt Water Systems
pa_burst-pressure-psi	4
pa_construction-reinforcement	Braided
equal_to_aeroquip_no	Fc133-20
hose_id	'1-1/4
pa_hose-size-dash-no	'-20
drawing_number	C18443-5
pa_layers-reinforcement	'3
Material	Synthetic Rubber Tube And Cover Reinforced With Synthetic Fiber
pa_max-dimension-a-in	'1.289

pa_max-dimension-b-in	'2.069
pa_mil-spec	Mil-Dtl-24136/2
pa_min-bend-radius-in	'16.00
pa_min-dimension-a-in	'1.211
pa_min-dimension-b-in	'1.975
pa_nsn-no	4720-00-167-4726
weight_per_ft_lbs	'1.26
pa_working-pressure-psi	'1

HYDRASEARCH