

HS133-24 – HS133 Series – High Pressure Hoses

SKU: HS133-24



Description

- Use with Hydrasearch HS1489 Series Fittings. Materials: Synthetic rubber tube and cover reinforced with synthetic fiber. Application: Fresh and salt water systems, hydraulic systems, fuel systems, oil applications and low pressure air. Operating Temperature Range: -40°F to +200°F
- Equal to: FC133
- Mil Number: DTL-24136/2

Specification Table

pa_applicable-fittings	Hs1489
application	Fresh And Salt Water Systems
pa_burst-pressure-psi	4
pa_construction-reinforcement	Braided
equal_to_aeroquip_no	Fc133-24
hose_id	'1-1/2
pa_hose-size-dash-no	'-24
drawing_number	C18443-6
pa_layers-reinforcement	'3
Material	Synthetic Rubber Tube And Cover Reinforced With Synthetic Fiber
pa_max-dimension-a-in	1.539

pa_max-dimension-b-in	2.297
pa_mil-spec	Mil-Dtl-24136/2
pa_min-bend-radius-in	'20.00
pa_min-dimension-a-in	1.461
pa_min-dimension-b-in	'2.203
pa_nsn-no	4720-01-019-8976
weight_per_ft_lbs	1.34
pa_working-pressure-psi	1

HYDRASEARCH