



information@hydrasearch.com
+1.410.643.8900

3H-8794-16 – Medium Pressure Hoses

SKU: 3H-8794-16



Description

- In accordance with MIL-DTL-8794. Hydrasearch MS28741 medium pressure hose assemblies can be used as flexible connections on medium pressure power plant and airframe applications (see SAE-AIR797). They are especially suited for medium pressure hydraulic fluids, engine oils, fuels and coolant fluids. Hydrasearch medium pressure hose is used for applications with operating pressures up to 3000 PSI, and having a temperature range of -65°F to +250°F. See MIL-DTL-8794 for specific temperature ranges.

Specification Table

pa_approx-od-in	1.234
pa_construction	A. Inner Tube: Oil And Fuel Resistant Synthetic Compound. B. Reinforcement: Single Wire Braid And Single Cotton Braid. C. Outer Cover: Oil And Fuel Resistant Synthetic Impregnated Cotton
hose_size	1
pa_identification	Black Cover With Yellow Line Running Parallel To Bore Of Hose To Indicate Natural Lay Of Hose After Installing. The Specification Pin
max_operating_pressure_psi	800
pa_mil-spec	Mil-Dtl-8794
pa_min-bend-radius-in	7.375
pa_min-burst-pressure-psi	3
pa_min-hose-id-in	0.875
pa_nsn-no	4720-00-595-1088
pa_operating-systems	A. Severe Vibrating And Flexing. B. Resistant To Engine Oil And Cleaning Solvent Externally. C. Internal And External Temperatures From -65°F To +250°F. D. Internal Fluids
pa_proof-test-pressure-psi	1
weight_per_ft_lbs	0.43