



+1.410.643.8900

88B0100004F0000 – High Pressure Rubber Hose Assemblies

SKU: 88B0100004F0000



Description

Hydrasearch MS28759, flared, high pressure hose assemblies can be used as flexible connections on high
pressure power plant and airframe applications (see SAE-AIR797). They are especially suited for high pressure
hydraulic fluids, engine oils, fuels and coolant fluids. Hydrasearch high pressure hose is used for applications with
operating pressures to 3000 PSI, and having a temperature range of -65°F to +275°F (see MIL-DTL-8788 for
specific temperature ranges).

Specification Table

pa_finish	Aluminum Alloy
pa_fitting-mil-spec	Mil-Dtl-8789
pa_hose-assembly-mil-spec	Mil-Dtl-8790
pa_hose-mil-spec	Mil-Dtl-8788
hose_id	0.219
hose_size	1/4
Material	Aluminum And Steel In Accordance With Table I Of Mil-Dtl-8789.All Sizes Are Steel With Aluminum Sockets
max_operating_pressure_psi	3
pa_ms-part-no	Ms28759-4L
size_in	-04
pa_thread-size-t	7/16"-20
pa_notes	Dimensional Information Is For Reference Only. Variations From These Dimensions On Actual Parts May Occur As The Result Of Engineering Revisions.